

Table of Contents

1 Introduction

1.1 Purpose and Scope	1-1
1.2 Service Provider Role	1-1
1.3 Equipment Manufacturer Role	1-2
1.4 Application Guidelines	1-3
1.4.1 COs and Similar Facilities	1-3
1.4.2 Commercial Buildings	1-3
1.4.3 Non-Environmentally Controlled Locations	1-3
1.4.4 Other Locations	1-3
1.5 Reasons for GR-63-CORE, Issue 3	1-4
1.6 Structure and Use of This Document	1-4
1.7 Related Documents	1-5
1.8 Requirements Terminology	1-5
1.9 Requirement Labeling Conventions	1-6
1.9.1 Numbering of Requirement and Related Objects	1-6
1.9.2 Requirement, Conditional Requirement, and Objective Identification	1-7

2 Spatial Requirements

2.1 General Requirements	2-1
2.1.1 Equipment Frame Floor Plans	2-3
2.1.2 NEBS Data (ND)	2-3
2.2 Equipment Frames	2-6
2.2.1 Vertical Space Allocation in an Equipment Frame Area	2-6
2.2.2 Equipment Frame Dimensions	2-7
2.2.2.1 Equipment Frame Dimensions - Open Style Racks	2-9
2.2.2.2 Equipment Frame Dimensions - Other Rack Styles	2-9
2.2.2.3 Equipment Frame Dimensions - Special Cases	2-10
2.2.2.4 Equipment Frame Cable Management Provisions	2-11
2.2.2.5 Equipment Frame Interface with Cable Rack	2-11
2.2.3 Equipment Frame Lineup Conformity	2-12
2.2.4 Equipment Frame Floor Loading	2-12
2.2.5 AC Convenience Outlets Within Equipment Frames	2-14
2.3 Distributing and Interconnecting Frames	2-14
2.3.1 Distributing Frames (DFs)	2-14
2.3.2 Interconnecting Frames (IFs)	2-15
2.4 DC Power Plant Equipment	2-16
2.4.1 Centralized DC Power Plant Equipment	2-16
2.5 Cable Distribution Systems (CDSs)	2-17
2.5.1 CDS Requirements	2-18
2.5.1.1 General	2-18
2.5.1.2 Overhead Cable Distribution	2-18
2.5.1.3 Cable Distribution Under Raised Floor	2-18
2.5.2 Cable Pathways Over Equipment Frame Areas	2-19
2.5.2.1 Elements of Allocation Plan	2-19
2.5.2.2 System Cable Racks	2-20
2.5.2.3 Via Cable Racks	2-21

- 2.5.2.4 Lights 2-21
- 2.5.3 Cable Pathways Over Distributing Frame (DF) Areas 2-21
- 2.5.4 CDS Floor Load and Support 2-21
- 2.6 Operations Systems (OSs) 2-22
- 2.7 Cable Entrance Facility (CEF) 2-23
 - 2.7.1 CEF Spatial Requirements 2-23
 - 2.7.2 CEF Loading Requirements 2-23
 - 2.7.3 CEF Equipment Temperature and Humidity Requirements 2-23
- 2.8 Summary of Equipment Allocations 2-24

3 NEBS-2000 Framework Criteria

4 Environmental Criteria

- 4.1 Temperature, Humidity, and Altitude Criteria 4-1
 - 4.1.1 Transportation and Storage Environmental Criteria 4-1
 - 4.1.1.1 Low-Temperature Exposure and Thermal Shock 4-2
 - 4.1.1.2 High Relative Humidity Exposure 4-2
 - 4.1.1.3 High-Temperature Exposure and Thermal Shock 4-3
 - 4.1.2 Operating Temperature and Humidity Criteria 4-3
 - 4.1.3 Altitude 4-5
 - 4.1.4 Temperature Margin Evaluation 4-5
 - 4.1.5 Fan Cooled Equipment Criteria 4-6
 - 4.1.6 Heat Dissipation 4-6
 - 4.1.7 Surface Temperature 4-8
 - 4.1.8 Equipment Airflow 4-9
- 4.2 Fire Resistance 4-11
 - 4.2.1 Fire-Resistance Rationale 4-11
 - 4.2.2 Equipment Assembly Fire Tests 4-11
 - 4.2.2.1 Frame-Level Fire-Resistance Criteria 4-12
 - 4.2.2.2 Shelf-Level Fire-Resistance Criteria 4-13
 - 4.2.2.3 Smoke and Self-Extinguishment Criteria 4-14
 - 4.2.3 Use of Fire-Resistant Materials, Components, Wiring, and Cable 4-15
 - 4.2.3.1 Material/Components Fire-Resistance Criteria 4-15
 - 4.2.3.2 Cable Distribution Assemblies 4-17
 - 4.2.4 Smoke Corrosivity 4-18
 - 4.2.4.1 Optical Fiber Cable Trays and Raceways 4-18
- 4.3 Equipment Handling Criteria 4-19
 - 4.3.1 Packaged Equipment Shock Criteria 4-19
 - 4.3.1.1 Category A Containers 4-20
 - 4.3.1.2 Category B Containers 4-20
 - 4.3.2 Unpackaged Equipment Shock Criteria 4-20
- 4.4 Earthquake, Office Vibration, and Transportation Vibration 4-21
 - 4.4.1 Earthquake Environment and Criteria 4-21
 - 4.4.1.1 Earthquake Environment 4-21
 - 4.4.1.2 Physical Performance Criteria 4-23
 - 4.4.1.3 Functional Performance 4-24
 - 4.4.2 Framework and Anchor Criteria 4-24
 - 4.4.3 Wall-Mounted Equipment Anchor Criterion 4-26
 - 4.4.4 Office Vibration Environment and Criteria 4-26
 - 4.4.4.1 Office Vibration Environment 4-26



4.4.4.2	Physical Performance Criteria	4-26
4.4.4.3	Functional Performance Criteria	4-26
4.4.5	Transportation Vibration Criteria	4-27
4.4.5.1	Transportation Environment	4-27
4.5	Airborne Contaminants	4-27
4.5.1	Contamination Classes	4-28
4.5.2	Contamination Levels	4-29
4.5.2.1	Environmentally Controlled Space	4-29
4.5.2.2	Outside Plant (OSP) Equipment	4-31
4.5.3	Measurement of Contaminant Levels	4-32
4.5.4	Equipment - Fan Filters	4-32
4.6	Acoustic Noise	4-33
4.7	Illumination	4-35
4.7.1	Illumination Criteria for Central Office (CO) Lighting Systems	4-35
4.7.1.1	Quantity of Light	4-35
4.7.1.2	Luminance Ratios	4-36
4.7.1.3	Color of Light	4-37
4.7.2	Illumination Criteria for Network Equipment	4-37
4.7.2.1	Surface Reflectance and Color	4-37
4.7.2.2	Glare	4-37

5 Environmental Test Methods

5.1	Temperature, Humidity, and Altitude Test Methods	5-1
5.1.1	Transportation and Storage Test Methods	5-3
5.1.1.1	Low-Temperature Exposure and Thermal Shock	5-4
5.1.1.2	High Relative Humidity Exposure	5-5
5.1.1.3	High-Temperature Exposure and Thermal Shock	5-6
5.1.2	Operating Temperature and Relative Humidity	5-7
5.1.3	Operating Altitude	5-11
5.1.4	Temperature Margin Determination	5-13
5.1.5	Operation with Fan Failure	5-14
5.1.6	Surface Temperature Test Procedures	5-14
5.1.6.1	Infrared Measurement Equipment	5-14
5.1.6.2	Contact Measurement Equipment	5-15
5.1.6.3	Equipment Evaluation Procedures	5-15
5.2	Fire Test Methods	5-16
5.2.1	Testing Clarification - Circuit Board Removal	5-16
5.2.1.1	Case 1 - No Mezzanine Cards	5-16
5.2.1.2	Case 2 - Mezzanine Card	5-17
5.2.1.3	Case 3 - Larger or Multiple Mezzanine Cards	5-18
5.2.2	ANSI T1.319-2003 Test Deviation - Fan Powering Options	5-19
5.2.3	Telcordia Needle Flame Test	5-20
5.2.3.1	Application to Individual Components	5-20
5.2.3.2	In-Situ Application to Individual Components	5-20
5.2.4	Guidelines for Retesting to Address Product Changes	5-21
5.2.5	Test Reporting - Additions	5-22
5.3	Handling Test Methods	5-23
5.3.1	Handling Drop Tests - Packaged Equipment	5-24
5.3.2	Unpackaged Equipment Drop Tests	5-28
5.4	Earthquake, Office Vibration, and Transportation Vibration Test Methods	5-32

- 5.4.1 Earthquake Test Methods 5-32
 - 5.4.1.1 Test Plan 5-34
 - 5.4.1.2 Laboratory Equipment 5-35
 - 5.4.1.3 Test Configuration 5-37
 - 5.4.1.4 Static Test Procedure 5-39
 - 5.4.1.5 Waveform Test Procedure 5-39
 - 5.4.1.6 Test Report 5-40
- 5.4.2 Office Vibration Test Procedure 5-40
- 5.4.3 Transportation Vibration—Packaged Equipment 5-41
- 5.5 Airborne Contaminants Test Methods 5-43
 - 5.5.1 Scope 5-43
 - 5.5.2 Gaseous Contaminants Test Method 5-43
 - 5.5.2.1 Two Cleaning Procedures for Copper Coupons 5-47
 - 5.5.2.2 Test Procedure 5-49
 - 5.5.2.3 Measuring Parameters 5-50
 - 5.5.2.4 Safety Procedures for Testing Gaseous Contaminants 5-51
 - 5.5.2.5 Performance Criteria 5-51
 - 5.5.2.6 Test Report 5-51
 - 5.5.3 Hygroscopic Dust Test Method 5-55
 - 5.5.3.1 Sample Selection 5-55
 - 5.5.3.2 Test Sequence 5-55
 - 5.5.3.3 Performance Criteria 5-56
 - 5.5.3.4 Test Report 5-56
- 5.6 Acoustical Measurement Methodology 5-57
 - 5.6.1 Procedure for Nominal, 27°C (81°F) Operating Conditions: Test Room at 27°C (81°F) 5-57
 - 5.6.2 Procedure for Nominal, 27°C (81°F) Operating Conditions: Test Room at Other Than 27°C (81°F) 5-58
 - 5.6.3 Procedure for Nominal, 23°C (73°F) Operating Conditions 5-58
 - 5.6.4 Procedure for High-Temperature Operating Conditions 5-58
- 5.7 Lighting Test Methods 5-58
 - 5.7.1 Test 1 - Equipment Assembly - Readability, Glare, and Reflectance Tests 5-59
 - 5.7.2 Test 2 - Console Illumination, Readability, and Glare Tests 5-63
 - 5.7.3 Test 3 - Lighting System Tests 5-65

Appendix A: References

- A.1 Telcordia Documents A-1
- A.2 Other Referenced Documents or Material A-2

Appendix B: Acronyms

Requirement-Object Index

List of Figures

Figure 2-1	Framework Base (Typical) — Floor Anchoring Hole Pattern	2-2
Figure 2-2	Typical 6-Lineup Floor Plan for Nominal 300 mm (12-in) Deep Frames	2-4
Figure 2-3	Typical 4-Lineup Floor Plan for Nominal 460 mm (18-in) Deep Frames	2-5
Figure 2-4	Typical Equipment Frame Area (Vertical Section)	2-7
Figure 2-5	Equipment Frame — Overall Dimensions	2-8
Figure 2-6	Typical Equipment Area Using Frames 1829 mm (6 ft, 0 in) High, 762 mm (2 ft, 6 in) Wide, and 610 mm (2 ft, 0 in) Deep	2-11
Figure 2-7	Typical Adapter Plate, Spacer, and Hole Locations in the Top of the Framework	2-13
Figure 2-8	Typical Network Distribution Frame Area	2-15
Figure 2-9	Typical Network DC Centralized Power Plant Equipment Area	2-16
Figure 2-10	Typical Cable Pathways for 305-mm (12-in) Deep Frame Areas (Conventional Cooling System - Air Diffusers)	2-20
Figure 2-11	Typical Cable Pathways for a Distributing Frame Area	2-22
Figure 4-1	Ambient Temperature and Humidity Limits	4-4
Figure 4-2	Profile View of Conforming Equipment Airflow Schemes Dashed Method Is Preferred	4-10
Figure 4-3	Telcordia Earthquake Zone Map	4-23
Figure 4-4	Transportation Vibration Environment	4-27
Figure 5-1	Low-Temperature Exposure and Thermal Shock	5-4
Figure 5-2	High Relative Humidity Exposure	5-5
Figure 5-3	High-Temperature Exposure and Thermal Shock	5-6
Figure 5-4	Operating Temperature and Humidity - Temperature vs. Time for Frame-Level Test	5-9
Figure 5-5	Temperature and Humidity Sensor Locations for Frame-Level Test	5-10
Figure 5-6	Card Removed and Burner Inserted in Plane of PWB	5-17
Figure 5-7	Parent PWB Removed and Burner Inserted - Mezzanine Card Left in Place	5-18
Figure 5-8	Mezzanine Card Removed and Burner Inserted	5-19
Figure 5-9	Drop Surfaces for Category A Container	5-25
Figure 5-10	Test Set-Up for Category A Container	5-26
Figure 5-11	Drop Surface for Category B Container	5-27
Figure 5-12	Category B Container - Equipment Handling Drops	5-28
Figure 5-13	Drop Surfaces for Circuit Pack	5-29
Figure 5-14	Drop Surfaces for Equipment Less Than 25 kg	5-30
Figure 5-15	Drop Surfaces for Equipment More Than 25 kg	5-31
Figure 5-16	Unpackaged Rotational Drops for Equipment More Than 25 kg	5-31
Figure 5-17	Earthquake Synthesized Waveform - VERTEQII- Zone 4	5-33
Figure 5-18	Required Response Spectra	5-34
Figure 5-19	Transportation Vibration Environment	5-42
Figure 5-20	Sample Test Report (Sheet 1 of 2)	5-53
Figure 5-20	Sample Test Report (Sheet 2 of 2)	5-54
Figure 5-21	Test 1 - Equipment Assembly, Readability, and Glare	5-61
Figure 5-22	Test 1 - Equipment Assembly, Surface Reflectance	5-62

Figure 5-23 Console Illumination, Readability, and Glare 5-64
Figure 5-24 Lighting System Test 3, Equipment Distribution Frame Areas . . 5-66
Figure 5-25 Lighting System Test 3, Power and Cable Entrance Areas 5-67

List of Tables

Table 2-1	Vertical Space	2-6
Table 2-2	Summary of Equipment Space and Load Allocations	2-24
Table 4-1	Low-Temperature Exposure and Thermal Shock	4-2
Table 4-2	High Relative Humidity Exposure	4-2
Table 4-3	High-Temperature Exposure and Thermal Shock	4-3
Table 4-4	Ambient ¹ Temperature and Humidity Limits	4-4
Table 4-5	Equipment Area Heat Release Objective	4-8
Table 4-6	Temperature Limits of Touchable Surfaces	4-9
Table 4-7	Category A Container Packaged Equipment Shock Criteria	4-20
Table 4-8	Category B Container Packaged Equipment Shock Criteria	4-20
Table 4-9	Unpackaged Equipment Shock Criteria	4-21
Table 4-10	Correlation of Earthquake Risks	4-22
Table 4-11	Outdoor Contaminant Levels	4-30
Table 4-12	Indoor Contaminant Levels	4-31
Table 4-13	Acoustical Noise Emission Limits	4-34
Table 4-14	Minimum Maintained Illumination Level	4-36
Table 5-1	Application Criteria for Needle Flame Test	5-20
Table 5-2	Response Spectrum Analyzer Frequencies	5-36
Table 5-3	Configuration Guidelines for Shelf-Level Testing	5-38
Table 5-4	Transportation Vibration Test Severity	5-42
Table 5-5	Typical Coupon Weight Gains During MFG Exposures	5-48
Table 5-6	Target Air Composition and Duration of MFG Testing for Equipment Designated for Indoor or Outdoor Use	5-50